

(Antistatic) General Purpose Hose (20 bar)

H.T. - MULTI PURPOSE - ANTISTATIC - WP 20

GENERAL PURPOSE LONG LENGTH HOSE SUITABLE FOR:

- Gases and fluids for applications where an antistatic hose is required
- Paints with solvents not containing aromatic, aliphatic and chlorinated hydrocarbons
- Acids, saline solutions, alcohol, marine water
- Fuels - hydrocarbons
- Hot water up to +120°C

TEMPERATURE RANGE:

-40°C to +120°C

CONSTRUCTION:

TUBE - Black, smooth resistant conductive EPDM rubber

REINFORCEMENT - High strength, synthetic textile yarn

COVER - Black, abrasion weathering and ozone resistant EPDM rubber

SURFACE - Smooth, extruded rubber

Part No.	Hose Inside Diameter		Hose Outside Diameter		Working Pressure		Burst Pressure		Weight kg/kg/m
	inch	mm	mm	bar	psi	bar	psi	kg/m	
GPH06X14	1/4"	6	14	20	300	60	900	0.20	
GPH10X19	3/8"	10	19	20	300	60	900	0.26	
GPH13X22	1/2"	13	22	20	300	60	900	0.27	
GPH19X29	3/4"	19	29	20	300	60	900	0.47	
GPH25X36	1"	25	36	20	300	60	900	0.65	

Other diameters and / or pressures are available on request.
N.B. The technical data and characteristics could change without warning

May 2023